



# WE BUILD WITH YOU

ESTB 1993

What we build can last for years. But what we do can last forever





#### TAIZHOU JULI TOOLS CO.,LTD.

ADD:Xuan Men Industrial Estate, Yuhuan,
Taizhou, Zhejiang Province, 317608, China
Tel:+86-576-87301677/87301678 Fax:+86-576-87301690
Http://www.zuppertools.com E-mail:sales@juli-tools.com







alogue for **Pa**y nbing too**l** 

YouTube



















### **HOW IT ALL BEGAN**

#### **START FROM THE YEAR OF 1993**

Since the company began from 1993, ZUPPER TOOL has experienced from "made in China" to "Created in China", We has become the leader of battery hydraulic tools in China more than 30 years

We build the tools for plumbing and heating installations last for years, but what we do can last forever. We manufacture best-in-class products by 350 strong highly trained team and sold over 100 countries.

We work continuously to improve the quality, efficiency and safety of our products to meet global market expectations and requirements. Accordingly many of our products are patented and comply with various international standards. ZUPPER products and you, together, WE BUILD.





#### **MORE THAN 30 YEARS OF EXPERIENCE**

# IMPORTANT EVENTS OF ZUPPER TOOLS

From 1993 until now, ZUPPER TOOL has experienced from "made in China" to "Created in China", We has become the leader of hydraulic tools in China more than 30 years

We build the electrical tools and tools for plumbing and heating installation last for years, but what we do can last forever.

1993

Yuhuan Hydraulic Tools Factory was established, which is the predecessor of ZUPPER TOOLS.

2003

JULI moved to a new factory, and entered the period of rapid development and regularization of enterprise development. 2011

"ZUPPER" brand was born, and get Madrid certification

2012

Draft the industry standard of "crimping tool for cables" and "manual cable cutter" 2015

2014

To be Recognized as High and new tech enterprises

Implement 5S site management and production management

2021

Provincial hidden champions enterprise

2022

ceremony

Parts products gain certificate ZHEJIANG MADE"PIN" National specialized and sophisticated enterprise--"Little giants"

玉工牌工具

1994

"Yugong" brand was recognized as
"China market protection brand"
by China Light Industry Product Quality
Assurance Center

2008

JULI cooperated with Zhejiang University to develop battery hydraulic tools 2020
Get the certifica


2019

Scheme ERP program, set up provincial testing lab

Get the certificate of intellectual property rights







### **CERTIFICATES FOR PRODUCT QUALITY AND MANAGEMENT**



#### **ZUPPER for enhanced safety and optimized standards**

For us, just meeting the standard is not enough, in terms of safety, efficiency and reliability. We are approved by ISO9001, ISO14001, ISO45001 certificates, and CE, UKCA, RoHS by TUV.



#### More than 100 PATENTS

Including intention patent 22 items, Utility model patent 35items. Our highly skilled development team works constrantly on practical and innovative solutions. We designed and developed with safety, efficiency and durability as our core concepts.

#### **ESTB 1993**



### TOP QUALITY FROM PRECISION PRODUCTION

To ensure the stability and high quality of our products, we purchase raw materials and components that guarantee first-class quality. We have more than 300 processing modern equipment; the latest CNC machines guarantee precision manufacturing for all tool components. The most important part is the key parts and processes of the product are completed in the factory to ensure that each product of the world class level.



### TOP QUALITY FROM MULTIPLE DEPTH INSPECTION

We build Precision Hydraulic Tool Research Institute to test raw material and important components, the only one in Zhejiang Province, it includes spectrometer, three coordinate measuring instruments, Keyence 3D scanner, Salt spray tester, profile meter, Image measuring instrument and spring testing and so on.

#### ESTB 1993


### CONTENT

BATTERY POWERED 10-34 PRESS TOOL	
ELECTRICAL POWERED 35-37 PRESS TOOL HAND-OPERATED HYDRAULIC PRESS TOOL	
BATTERY PUMP 40-41  CORDLESS TUBING CUTTER 42  CORDLESS TUBE EXPANDING TOOL 43	
BATTERY POWERED  AXIAL PRESS TOOL  44-49	
MANUAL TOOL 50-54	
BENDING TOOL 55	
PRESS JAWS 56-63	





TO BE MORE SMART TO BE MORE SLIM



- Ergonomic design with light weight, easily work overhead and in tight spaces
- The indicator light, with green indicating completion of press cycle, and red indicating press error or tool malfunction
- Only 2-4S to finish one cycle press
- SERVICE INTERVAL 10000 cycles




350° rotating head



LED indicator
For illumination



Manual Retract if Need



LED indicator
For showing tool status, warning

111

All Tools can be Controlled by One Trigger

Anti-slip Handle

OLED Display Show Press Cycles, Power, Errors Info

**Battery Lock** 

High Performance 18v Li-ion Battery







### **SL-1930 Battery Powered Press Tool**

- 12-35mm Stainless steel pipe
- 12-35mm(1/2"-1 3/8") Copper pipe
- 16-40mm PEX&Multi-layer composite pipe

The ZUPPER SL series with latest technology, updated structure and extended lifetime. It is slim and smart, really a good choice with in-line grip.



BATTERY POWERED PRESS TOOL



COPPER PIPE

MULTI-LAYER COMPOSITE PIPE





PEX PIPE

STAINLESS STEEL PIPE







12-35mm Stainless steel pipe	Battery:	18V Li-ion 2.0	Ah
12-35mm(1/2"-1 3/8") Copper pipe	Battery Charger:	AC 100V-240\	/ 50-60Hz
16-40mm PEX&Multi-layer composite pipe	Charging Time:	Approx. 40mi	ns
19kN	Service Interval:	10000cycles	
30mm	Weight:		
Approx. 35ml			
2-4S	Tool Size:	409×119×76r	nm
180cycles (DN 20 Stainless Steel)			
Description		Weight (KGS)	Standard Pack
SL-1930 Battery Press Tool Kit with	hout jaws		1set
18V, 2.0 Ah Li-Ion Batteries		0.3	2pcs
Charger		0.5	1pc
Plastic case		1.7	1pc
Sealing ring of cylinder:			1set
0 11 1 1 1 1			
	12-35mm(1/2"-13/8") Copper pipe 16-40mm PEX&Multi-layer composite pipe 19kN 30mm Approx. 35ml 2-4S 180cycles (DN 20 Stainless Steel)  Description SL-1930 Battery Press Tool Kit wit 18V, 2.0 Ah Li-lon Batteries Charger Plastic case Sealing ring of cylinder:	12-35mm(1/2"-13/8") Copper pipe 16-40mm PEX&Multi-layer composite pipe 19kN Service Interval: 30mm Weight: Approx. 35ml 2-4S Tool Size: 180cycles (DN 20 Stainless Steel)  Description SL-1930 Battery Press Tool Kit without jaws 18V, 2.0 Ah Li-lon Batteries Charger Plastic case	12-35mm(1/2"-13/8") Copper pipe Battery Charger: AC 100V-240V 16-40mm PEX&Multi-layer composite pipe Charging Time: Approx. 40min 19kN Service Interval: 10000cycles 30mm Weight:  Approx. 35ml 2-4S Tool Size: 409×119×76m 180cycles (DN 20 Stainless Steel)  Description Weight (KGS)  SL-1930 Battery Press Tool Kit without jaws 18V, 2.0 Ah Li-lon Batteries 0.3 Charger 0.5 Plastic case 1.7 Sealing ring of cylinder:

#### SL-2430 Battery Powered Press Tool

24kN Powerful output
MAX press φ35mm stainless steel pipe
2.3KGS Portable and convenient





MULTI-LAYER COMPOSITE PIPE

PEX PIPE

STAINLESS STEEL PIPE




**UPDATE** 

Technical Data			
Capacity:	12-35mm Stainless steel pipe	Pressing cycles/charge:	180 cycles (DN20 Stainless Steel)
	12-35mm(1/2"-1 3/8") Copper pipe	Battery:	18V 2.0Ah Li-ion
	16-40mm PEX&Multi-layer composite pipe	Charging voltage:	AC100-240V 50-60Hz
Rated pressure:	24kN	Charging time:	Approx.40mins
Rated power:	270W	Service interval:	10000cycles
Stroke:	30mm	Weight:	
Pressing cycle time:	2.5-5s	Tool size:	408x119x76mm

Model No.	Description	Weight (KGS)	Standard Pack	
SL-2430	SL-2430 Battery Press Tool kit without jaws		1set	
SL-2430	18V 2.0Ah Li-ion Batteries	0 <b>.</b> 3Kgs	2pcs	
	Charger	0 <b>.</b> 5Kgs	1pc	
Accessories	Plastic case	1 <b>.</b> 7Kgs	1pc	
	Sealing ring		1set	



# SMALLER, FASTER, LIGHTER COMPACT MEASURES HUGE POWER



#### THE RIGHT TOOL FOR YOUR NEEDS

- CIRCUIT BOARD DIAGNOSTICS

  Alart you when the battery is low or the tool is too hot or cold
- OLED DISPLAY
- Easy reading on
- Battery Percentage
- Pressing Times
- Fault Code
- Maintenance Note



- 180°SWIVELLING BARREL Easy access to connections
- TWO STAGE HYDRAULIC SYSTEM
  Hydraulic Ram Output provides more force for reliable connection
- ERGONOMIC DESIGN
  With light weight and inline grip, easily work overhead and in tight spaces.
- SERVICE INTERVAL: 10000 Cycles



CIRCUIT BOARD DIAGNOSTICS
Alart you when the battery is low or the tool is too hot or cold





#### PZ-1930 **Battery Powered Press Tool Precise pressing with lighter body**

- 12-35mm Stainless steel pipe
- 12-35mm(1/2"-1 3/8") Copper pipe
- 16-40mm PEX&Multi-layer composite pipe The PZ-1930 is mini press tool with in-line grip, it is efficient and reliable way to join copper, stainless steel and PEX & Multi-layer Pipe.



BATTERY POWERED PRESS TOOL



MULTI-LAYER COMPOSITE PIPE





PEX PIPE STAINLESS STEEL PIPE







Specifications					
Capacity:	12-35mm Stainless steel pipe	Battery:	18V Li-ion 2.0Ah		)Ah
	12-35mm(1/2"-1 3/8") Copper pipe	Battery Charge	r:	AC 100V-240	V 50-60Hz
	16-40mm PEX&Multi-layer composite pipe	Charging Time: Approx		Approx. 40mi	ns
Output:	19kN	Service Interval: 10000cycle		10000cycles	
Stroke:	30mm	Weight:		Approx.2.0kg	s (tool with battery)
Oil capacity:	Approx. 60ml			Approx. 3.5kg	gs(tool with battery and jaw)
Pressing cycle time:	2-4S	Tool Size:		363×119×75r	mm
Pressing cycles/charge:	180cycles (DN 20 Stainless Steel)				
Model No.	Description		We	eight (KGS)	Standard Pack
PZ-1930	PZ-1930 Battery Press Tool Kit without	iaws		4.5	1set
	18V, 2.0 Ah Li-Ion Batteries			0.3	2pcs
	Charger			0.5	1pc
ACCESSORIES	Plastic case			1.7	1pc
	Sealing ring of cylinder:				1set
	Sealing ring of safety valve:				1set

#### PZ-2430 **Battery Powered Press Tool**

24kN Powerful output MAX press φ35mm stainless steel pipe 2.2KGS Portable and convenient

- Quality guaranteed Core parts are general utilization and standardization
- Ergonomic design With light body
- OLED display shows battery percentage, press cycles, fault code, maintenance note





MULTI-LAYER COMPOSITE PIPE



PEX PIPE



STAINLESS STEEL PIPE







Specifications					
Capacity:	12-35mm Stainless steel pipe	Pressin	g cycles/charge:	180cylces(φ20m	nm stainless steel pipe
	12-35mm(1/2"-1 3/8") Copper pipe	Battery:		18V 2.0Ah Li-ion	1
	16-40mm PEX&Multi-layer composite pipe	Chargin	ig voltage:	AC100-240V 50-	-60Hz
Rated pressure:	24kN	Chargin	ig time:	Approx.40mins	
Rated power:	270W	Service interval:		10000cycles	
Stroke:	30mm	Weight:		3.38kgs(tool with battery and jaw)	
Pressing cycle time:	2.5-5S	Tool size:		362x122x76mm	
Accessories					
Model NO.	Description		Wei	ght	Standard pack
D7 2/20	PZ-2430 Battery Press Tool kit without jaws		4.7Kgs		1set
PZ-2430	18V 2.0Ah Li-ion Batteries	0.3Kgs		Kgs	2pcs
	Charger	0.5Kgs		1pc	
Accessories	Plastic case	1.71		Kgs	1pc
	Sealing ring				1set



#### **BZ-1930 Battery Powered Press Tool**

improved ergonomic design and huge power in zupper hydraulic system

- Ergonomic designed with 30cm length and 2kgs lightweight, comfortable operation.
- The spare parts are made of high quality aviation aluminum
- Only 4-6S to finish one cycle press
- The tool includes two 18V, 2.0Ah Li-ion and one charger
- It is actuated by motor and controlled by MCU, with two stage hydraulic system.
- SERVICE INTERVAL 10000 cycles





















Specifications					
Capacity:	12-35mm Stainless steel pipe	Battery:		18V Li-ion 2.	.0Ah
	12-35mm(1/2"-1 3/8") Copper pipe	Battery Chai	rger:	AC 100V-24	0V 50-60Hz
	16-40mm PEX&Multi-layer composite pipe	Charging Tir	ne:	Approx. 40m	nins
Output:	19kN			10000cycles	5
Stroke:	30mm	Weight: App		Approx.2.4kgs (tool with battery)	
Oil capacity:	Approx. 60ml	Approx. 3.9		kgs(tool with battery and ja	
Pressing Cycle Time:	4-6S	Tool Size:		300×276×75	mm
Pressing Cycles/charge:	180cycles (DN 20 Stainless Steel)				
Model No.	Description		Wei	ght (KGS)	Standard Pack
BZ-1930	BZ-1930 Battery Press Tool Kit without j	aws		6.20	1set
	18V, 2.0Ah Li-Ion Batteries			0.3	2pcs
	Charger			0.5	1pc
ACCESSORIES	Plastic case			2.90	1pc
	Sealing ring of cylinder:				1set
	Sealing ring of safety valve:				1set



21





#### PZ-3240 **Battery Powered Press Tool**

#### THE MOST DURABLE INTELLIGENT PRESS TOOL

**☑** LONGER WARRANTY 2years or 40000cycles

BATTERY POWERED PRESS TOOL

**☑** OPTIONAL EXTENDED FUNCTIONS

Brushless motor / Pressure sensor / Bluetooth

180° SWIVELLING BARREL Easy access to connections







MULTI-LAYER COMPOSITE PIPE





STAINLESS STEEL PIPE

Specifications			
Capacity:	12-54mm for stainless steel pipe	Pressing cycles/charge:	350cycles(DN 20 Stainless Steel)
	12-108mm(1/2"-4") for PEX,Multi-layer composite	Battery:	18V Li-ion 4.0Ah
	and copper pipe	Charging time:	Approx.80mins
Output:	32kN	Charging voltage:	AC 100V-240V 50-60Hz
Stroke:	40mm	Service interval:	10000cycles
Pressing cycle time:	3-6s(depends on the dia of pipe)	Weight:	4.1kgs(tool with battery)
Tool Size:	495x89x123mm		6.2kgs(tool with battery and jaw)

#### **ED-5050 Battery Powered Press Tool**

For thick stainless steel, copper

- Designed with matching press jaws
- Cylinder is made of steel, Longer span life
- Two stage hydraulic system, high-efficiency
- OLED Display shows battery percentage, pressing times, fault code, maintenance note.

#### PZ-5050 **Battery Powered Press Tool**

For thick stainless steel, copper

- Cylinder is made of high strength steel,longer span life
- Aerometal ram with matching press jaws, suit for thick pipe connections
- New design conform to ergonomics and optimized position of centre of gravity
- 180° swivelling barresl,easy access to connections
- Warranty 2years or 30,000cycles
- Brushless motor is optional, suit for inflammable and explosive field (professional test before using)
- Pressure sensor and Bluetooth wireless communication technology is optional







Specifications	ED-5050	PZ-5050
Pressing range:	12-54mm for stainless steel pipe	12-54mm for stainless steel pipe
	12-108mm(1/2"-4") for copper pipe,PEX,XPAP	12-108mm(1/2"-4") for copper pipe,PEX,XPAP
Rated pressure:	50kN	50kN
Stroke:	50mm	50mm
Time/work:	3-6s(depend on the dia of pipe)	3-6s(depend on the dia of pipe)
Cycles/charger:	180cycles	180cycles
Battery:	18V Li-ion 4.0Ah	18V Li-ion 4.0Ah
Charging voltage:	AC 100V-240V 50-60Hz	AC 100V-240V 50-60Hz
Charging time:	Approx.80mins	Approx.80mins
Service Interval:	10000cycles	10000cycles
Weight:	4.7kgs(with battery)	4.9kgs(with battery)

Battery Press Too	l Kit			
	ED-5050	Weight(kgs)	PZ-5050	Weight(kgs)
	Battery, 18V, 4.0Ah Li-Ion	0.6kgs	Battery, 18V, 4.0Ah Li-Ion	0.6kgs
ACCESSORRIES	Charger	0.5kgs	Charger	0,5kgs
	Plastic case	4.1kgs	Plastic case	4.1kgs





- Battery press tool with in-line grip.
- Only 3-4.5S to finish one cycle press
- The tool comes standard with two 18v,4.0Ah Lion-batteries and one charger. It can achieve over 350 cycles per charger.
- Motor drivers, Micro-computer control system, OLED screen and double valve hydraulic system.











LED Light





**ACCESSORRIES** 





Specificat	ions				
Capacity:	12-54mm for stainles	s steel pipe	Battery:	18V Li-i	on 4.0Ah
	12-108mm(1/2"-4") fo	or PEX,Multi-layer composite	Battery Charger:	AC 100	-240V
	and copper pipe		Charging Time:	Approx.	.80mins
Output:	32kN		Service Interval:	10000c	ycles
Stroke:	40mm		Weight:	Approx.3.9kgs (tool with battery)	
Cycle Time:	Approx. 3-4.5 second	S		Approx.	.6.1kgs(tool with battery and jaw)
Oil capacity:	115ml		Tool Size:	466×12	6×82mm
PZ-1550 B	lattery Press Too	ol Kit			
MODEL NO.		DESCRIPTION	DESCRIPTION		Weight(kgs)
PZ-1550		PZ-1550 Battery Press	PZ-1550 Battery Press Tool Kit without jaws		9.20
PZ-1000		Battery, 18V, 4.0Ah Li-	lon		0.60

Charger

Plastic case






# POWERFUL, RELIABLE AND SIMPLY PRACTICAL





#### THE RIGHT TOOL FOR YOUR NEEDS

- OLED Data Display to show crimping time, Electricity Quantity, maintenance reminding and fault code.
- Air Cooling Heat dissipation System to extend using life.
- Press head rotates 310°
- Two stage hydraulic system with fast feed and power control
- Quick motor stop guarantees highest safety for the operator
- Automatic retraction when crimp is completed
- Electronic control and monitor of crimping operation
- Ergonomic design and optimized position of centre of gravity



HIGH PERFORMANCE 18V Li-ion Battery

TWO STAGE HYDRAULIC SYSTEM

MANUAL RETRACT IF NEED

ALL TOOLS CAN BE CONTROLLED BY ONE TRIGGER

OLED DISPLAY



CIRCUIT BOARD DIAGNOSTICS Alart you when the battery is low or the tool is too hot or cold





### ED-1550 Battery Powered Press Tool

#### Faster & Reliable

The ED-1550 gives another option for a fast and reliable way to join copper, stainless steel and PEX pipe. The tool comes standard with two 18V, 4.0Ah Li-ion batteries and one charger, motor drives, Micro-computer control system, OLED screen and double valve hydraulic system, it can achieve over 350 cycles per charge.







3-85
PER CYCLE TIME



Specificat	ions				
Capacity:	12-54mm for stainless steel pipe		Battery:	18V Li-i	on 4.0Ah
	12-108mm(1/2"-4") fo	r PEX,Multi-layer composite	Battery Charger:	AC 100	-240V
	and copper pipe		Charging Time:	Approx.	80mins
Output:	32kN		Service Interval:	10000c	ycles
Stroke:	40mm		Weight:	Approx.	3.8kgs (tool with battery)
Cycle Time:	Approx. 3-8 seconds			Approx.6.0kgs(tool with battery and ja	
Oil capacity:	115ml		Tool Size:	394×326×84mm	
ED-1550 E	Battery Press Too	ol Kit			
MODEL NO.		DESCRIPTION			Weight(kgs)
ED 1550		ED-1550 Battery Pres	s Tool Kit without jaws		9.0
ED-1550 Battery, 18V, 4,0Ah Li-I		Ah Li-lon		0.6	
ACCECCORDICC		Charger			0.5
ACCESSORRIE	15	Plastic case			4.1



### HH-60100 Electrical Powered Press Tool For big size from 60-108mm

- stainless steel pipe
- Designed with matching press jaws
- Cylinder is made of steel, Longer span life
- Two stage hydraulic system, high-efficiency
- OLED Display shows battery percentage, pressing times, fault code, maintenance note.

### ED-60100 Battery Powered Press Tool For big size from 60-108mm


stainless steel pipe

- Designed with matching press jaws
- Cylinder is made of steel, Longer span life
- Two stage hydraulic system, high-efficiency
- OLED Display shows battery percentage, pressing times, fault code, maintenance note.



Specifications	HH-60100	ED-60100
Pressing range:	60-108mm(2"-4	4") for stainless steel pipe and copper pipe
Rated pressure:	80kN	80kN
Stroke:	80mm	80mm
Time/work:	10-25s(depend on the dia of pipe)	10-25s(depend on the dia of pipe)
Cycles/charger:		50cycles
Battery:		18V/5.0Ah
Battery Charger:		AC 100V-240V;50-60Hz
Charging Time:		Approx.100mins
Service Interval:	10,000cycles	10,000cycles
Weight:		

Battery Press Tool Kit				
	HH-60100	Weight(kgs)	ED-60100	Weight(kgs)
			Battery, 18V, 5.0Ah Li-Ion	0.6
ACCESSORRIES			Charger	0.5
	Plastic case	6.1	Plastic case	6.1



## NEW TECHNOLOGY OF EB SERIES BRUSHLESS MOTOR

No carbon brush, durability and reliability



#### **BRUSHLESS MOTORS ARE DRIVING REVOLUTIONARY PERFORMANCE**



LONGER **MOTOR LIFE** Longer life and maintenance-free thanks

to brushless technology

MORE **POWER** 

No carbon brush. When the motor is running, there is no power loss by friction and reduce the heat generated by the motor.

+30%

**MORE RUN-TIME** 

Heat generated by Brushless motor is small Compared to the brush motor, the brushless motor will do more work in the same full charge of the battery pack



**APPLICATION** 

No carbon brush, the motor does not produce sparks at work, it is more suitable used in combustible place



#### EB-1550 EB-32100 **Battery Powered Press Tool New Technology Brushless Motor**

- 3-6S to finish one cycle
- Automatic retraction when press is completed
- Two stage hydraulic system
- An ergonomic design and optimized position of center of gravity to provide increased feel and usability
- Micro computer control system



#### **Bluetooth And Pressure Sensor**

Thanks to new implemented Bluetooth technology, devicerelated data can be requested via the ZUPPER APP. The ZUPPER EB Series include BLUETOOTH asbasic configuration, you can choose pressure sensor at optional.

#### **ZUPPER Check-APP**

- Data transfer between press tool and APP
- See the location of where your ZUPPER Link enabled tool was
- Check the pressure by pressure sensor to differentiate the pressure normal or not,
- APP shows the pressure data counter to check and analyze the pressure easily.



Technical Data	EB-1550	EB-32100
Capacity:	12-54mm for stainless steel pipe	12-54mm for stainless steel pipe
	12-108mm(1/2"-4") for PEX,Multi-layer composite and copper pipe	12-108mm(1/2"-4") for PEX,Multi-layer composite and copper pipe
Output:	32kN	32kN
Stroke:	40mm	40/60/100mm(adjustable)
Cycle time:	3-6s(depands on diameter of pipe)	3-6s(depands on diameter of pipe)
Oil capacity:	115ml	250ml
Pressing cycles/charge	360cycles(DN20 stainless steel)	360cycles(DN20 stainless steel)
Battery:	18V Li-ion 4.0Ah	18V Li-ion 4.0Ah
Charger:	AC 100V-240V 50-60Hz	AC 100V-240V 50-60Hz
Charging time:	Approx.80mins	Approx.80mins
Service Interval:	10000cycles	10000cycles
Weight:	3.8kgs(tool with battery)	
	6.0kgs(tool with battery and jaw)	
Tool Size:	400x318x86mm	525x318x86mm

710000001100				
	EB-1550	Weight(kgs)	EB-32100	Weight(kgs)
	Battery Press Tool Kit without jaws:	9.0	Battery Press Tool Kit without jaws:	
Accessories:	18V Li-ion 4.0Ah	0.6	18V Li-ion 4.0Ah	0.6
Accessories:	Charger	0.5	Charger	0.5
	Plastic case	4.1	Plastic case	4.1

Kit includes: EB-1550 battery press tool, Two 4.0Ah Batteries, One Charger and Carrying case





#### **BZ-1550 Battery Powered Press Tool** 220V Lasting Power Supply High performance, Save time

- Battery press tool with gun type grip.Jaws are made of high strength forging steel.
- LED light for low or no-light environment
- LCD data display can show pressing times, electricity quantity and maintenance reminding information
- The tool comes standard with two 18v,4.0Ah Lion-batteries and one charger. It can achieve over 300 cycles per charger.
- Motor drivers, Micro-computer control system, and double valve hydraulic system.







STAINLESS STEEL PIPE







Specifications				
Capacity:	12-54mm for	stainless steel pipe	Battery:	18V Li-ion 4.0Ah
	12-108mm(1,	/2"-4") for PEX,Multi-layer composite	Charger:	AC 100V-240V 50-60Hz
	and copper p	ipe	Charging time:	Approx.80mins
Output:	32kN		Service Interval:	10000cycles
Stroke:	40mm		Weight:	4.5kgs(tool with battery)
Cycle time:	3-6s(depands on diameter of pipe)			6.7kgs(tool with battery and jaw)
Pressing cycles/charge	350cycles(DN20 stainless steel)		Tool Size:	375x329x85mm
Accessories:	ories:			
MODEL NO.		DESCRIPTION		Weight(kgs)
BZ-1550		BZ-1550 Battery Press Tool k	BZ-1550 Battery Press Tool Kit without jaws	
BZ-1330		18V Li-ion 4.0Ah		0.6
ACCECCODDIEC		Charger		0.5
ACCESSORRIES		Plastic case		4.1

Kit includes: BZ-1550 Press Tool, Two 4.0Ah batteries, One charger and carrying case



#### **MP-1930 Battery Powered Mechanical Press Tool**

- 12-35mm(1/2"-1 3/8") Copper pipe
- 16-40mm PEX & Multi-layer composite pipe

The MP-1930 is the newest addition of press tool with mechanical system, it is faster and efficient way to join metal pipe and plastic pipe

- The tool is easier to do maintenance
- With 180° rotatable head
- Enclosed screw structure prevents sand and dust
- Brushless motor with longer motor lift and more Run-time
- Screw Drive with high efficient, press more fast
- Ergonomic design, comfortable operation
- ONE KEY control switch, automatically completes press cycles
- The indicator light, with green indicating completion of press cycle, and red indicating press error or tool malfunction





STAINLESS STEEL PIPE








180° rotating head

Specifications				
Capacity:	12-28mm Stainless steel pipe(press jaw)	Battery:	18V Li-ion	2.0Ah
	15-35mm Stainless steel pipe(R8 angle jaw)	Battery Char	ger: AC 100V-2	40V 50-60Hz
	12-35mm(1/2"-1 3/8") Copper pipe	Charging Tim	ne: Approx. 40	mins
	16-32mm PEX&Multi-layer composite pipe	Weight:	Approx.2.4	kgs (tool with battery)
Output:	19kN	Tool Size:	400x119x7	'6mm
Stroke:	30mm			
Pressing Cycle Time:	2-4S			
Model No.	Description		Weight (KGS)	Standard Pack
MP-1930	MP-1930 Battery Press Tool Kit with	out jaws	4.9	1set
	18V, 2.0 Ah Li-Ion Batteries		0.3	2pcs
ACCESSORIES	Charger		0.5	1pc
	Plastic case		1.7	1pc



37





#### **CZ-1550 Electric Powered Press Tool**

- Only 3S to finish one cycle press
- Press jaw with piston, to avoid maloperation
- Anti-slip handle and an optimized center of gravity for easier carry.
- Motor drives, Micro-computer control system and double valve hydraulic system.







COPPER PIPE

MULTI-LAYER COMPOSITE PIPE





ELECTRIC POWERED PRESS TOOL

STAINLESS STEEL PIPE







Specifica	tions				
Capacity:	12-54mm for stainless steel pipe		Rated Power:	490V	V
	12-108mm(1/2"-4") for	12-108mm(1/2"-4") for PEX,Multi-layer composite and copper pipe		AC22	20V 50/60HZ (or AC 110V 50/60HZ)
Output:	32kN	32kN		4.1kg	gs(without jaw)
Stroke:	40mm		Tool Size:	456 x	(81 x 130mm
Cycle time:	3S(DN25)		Hydraulic oil:	Shell	l Tellus S2V HV15 130ml
Accessor	ies:				
MODEL NO.		DESCRIPTION			Weight(kgs)
CZ-1550		CZ-1550 Press Tool Kit without ja	aws		8.15
CZ-1550		Plastic case			3.2

#### HH-1550 **Electric Powered Press Tool**

520W High power 220V lasting power supply, Reliable and Stable

- Only 3S to finish one cycle press
- Press jaw with piston, to avoid maloperation.
- Anti-slip handle and an optimized center of gravity for easier carry.
- Motor drives, Micro-computer control system and double valve hydraulic system.









PEX PIPE

STAINLESS STEEL PIPE








Capacity:	12-54mm for stainless	steel pipe	Rated Power:	520W
	12-108mm(1/2"-4") for	PEX,Multi-layer composite and copper pipe	Voltage:	AC220V 50/60HZ (or AC 110V 50/60H
Output:	32kN		Service Interval:	10000cycles
Stroke:	40mm		Weight:	4kgs(without jaw)
Cycle time:	2 <b>.</b> 6-6S		Tool Size:	422×328×82mm
			Hydraulic oil:	Shell Tellus S2V HV15 240ml
HH-1550 F	Press Tool Kit			
MODEL NO.		DESCRIPTION		Weight(kgs)
HH-1550		HH-1550 Press Tool Kit without	jaws	7.2
		Plastic case		3.2











- Forged jaws with high strength, sturdy and durable
- 350° rotating head
- Two stage hydraulic system with fast feed and power stroke • Light weight due to high quality aluminum housing
- Automatic retraction when crimping is completed
- With safety valve to prevent pressure overload.

Technical data
Press range: 12-54mm(1/2"-2") for stainless steel pipe
12-108mm(1/2"-4") for PEX,Multi-layer and composite copper pipe
Rated press force: 32kN
Rated work pressure: 33Mpa
Stroke: 40mm
Package: Metal box



#### Hand-operated Hydraulic Press Tool

- 350° rotating head
- Two stage hydraulic system with fast feed and power stroke
- Light weight due to high quality aluminum housing
- Automatic retraction when crimping is completed
- With safety valve to prevent pressure overload.

Technical data		
Press range:	12-35mm Stainless steel pipe	
	12-35mm(1/2"-1 3/8") Copper pipe	
	16-40mm PEX&Multi-layer composite pipe	
Rated pressure:	19kN	
Stroke:	30mm	
Oil capacity:	48ml	
Tool size:	385x63.5x231mm	
Weight:	1 6kg(without jaws)	





For big size from  $60\sim108$ mm stainless steel pipe

Technical data		
Press range:	60-108mm(2-4")for stainless steel	l pipe and copper pipe
Rated work pres	ssure:	700bar(70MPa)
Stroke:		80mm
Oil capacity:		80ml
Tool size:		515x280x84mm
Weight:		9.3kgs(without jaw)
Package:		Metal box



FHT-3240 Hydraulic Press Head

- Forged jaws with high strength, sturdy and durable
- Hand pump,foot pump and electrical pump optional

Technical data	
Press range:	12-54mm(1/2"-2") for stainless steel pipe
12-108mm(1/2"-4"	) for PEX,Multi-layer composite and copper pipe
Rated press force:	32kN
Rated work pressure:	52Mpa
Stroke:	40mm
Package:	Metal box

38

HAND-OPERATED HYDRAULIC PRESS TOOL





#### **EB-700**

#### **Battery Powered Hydraulic Pump**

- Lightweight and portable design for outdoor work
- OLED display show Pressure value, Maintenance note, Battery percentage, Working cycles ect.
- Automatic retraction when operation is complete
- Manual retract if need
- Electronic sensor pressure control
- High performance 18V Li-ion battery
- Operates for crimping, cutting and punching heads
- All tools and hydraulic hose with couplers,easy and quick to connect







1.5m Hydraulic hose

1.5m Remote controller (Wireless remote control at optional) Carrying strap





Comfort Backpack















Specifications	
Oil Capacity:	Approx. 700ml
Pressure:	700bar(70Mpa)
Power:	490W
Voltage:	18.0V DC
Weight:	5.9kgs(with battery)
Tool size:	338x172x266mm
Battery:	5.0Ah Li-ion battery
Charging time:	100mins
Operation mode:	Remote control at 1.5 meters, or wireless remote control at 25 meters
Accessories	
Battery:	2pcs
Charger:	1pc
Strap:	1pc
Backpack:	1pc
Wireless control optional:	1pc with 1.5m wire
Oil tube:	1pc 1.5m







#### MC-1228 **Cordless Tubing Cutter**

For Stainless steel pipe, Copper pipe and uncoated carbon steel pipe from Φ**12-28mm** 

- The light weight tool is only 2.9KGS,easy for one handed operation.
- Convenience and fast,9S cut off φ20 Stainless steel pipe.
- Without burr and iron dust, clean after cutting.
- Auto-adjust dia from 12mm to 28mm.
- Build in LED light, to find the cutting position precisely.
- Easy to do pipe line maintenance in narrow space.













Specifications	
Cutting range:	< 1.5mm ø12-28mm
Voltage/capacity	18V/2.0Ah
Charging Time	Approx.40mins
Charging Voltage	AC100V-240V; 50-60Hz
Weight	2.9kgs(with battery)
Cycle time	9s(ø20mm Stainless steel pipe)
Cyles/charger	150cyles(ø20mm Stainless steel pipe)
Tool Size	385x76x128mm

#### **ME-1225**

#### **Cordless Tube Expanding Tool**

**Quick & Easy Connections for PEX-a material** 

- Faster to connect PEX ring to PEX-a pipe
  Compact and portable, weight 2.45KGS with battery, easy for one handed operation
- More than 70 expensions per charge

#### **Expanding heads** Cycles of expansions

16x1.8/2.2 20x1.9/2.0 4-6 cycles 6-8 cycles 25x2.3 8-12 cycles 32x2.9 22-25cycles

#### Suit for various projects



















#### **Expanding heads**















European standard

Ф25x2.3mm Ф20x1.9/2.0mm Ф16x1.8/2.2mm



Specifications	
Max expanding dia. and wall thickness range:	<25X3.5mm,<32X2.9mm
Voltage/capacity:	18V/2.0Ah
Charging Time:	Approx.40mins
Charging Voltage:	AC100V-240V; 50-60Hz
Weight:	2.45kgs(with battery)
Tool Size:	193x94x270mm
Standard expanding heads:	16x1.8/2.2mm,20x1.9/2.0mm,25x2.3mm





### **SL-1622**Battery Powered Axial Press Tool

For A/C Lock sleeve connection

- Ergonomic design, with light weight, easily work overhead and in tight spaces
- The indicator light, with green indicating completion of press cycle, and red indicating press error or tool malfunction
- Only 2-4S to finish one cycle press
- SERVICE INTERVAL 10000 cycles

BATTERY POWERED AXIAL PRESS TOOL





Specifications	
Output:	16kN
Stroke:	22mm
Suitable material:	Aluminum / Copper /Steel
Max connecting range:	Outer dia.16mm
Service interval:	10000cycles
Voltage of battery:	DC 18V,2.0Ah
Battery Charger:	AC 100V-240V 50-60Hz
Charging time:	Approx.40mins
Weight:	
Tool size:	463×132×76mm
Accessories:	
Battery:	2pcs
Charger:	1pc
Sealing ring of cylinder:	1set
Sealing ring of safety valve:	1set





### SL-1240PE Battery Powered Axial Press & Expand Tool

For axial press & expand Pex and Multi-layer composite pipe

Output:	18kN
Stroke:	39mm
Connecting range:	PEX pipe:16-32mm
	Multi-Layer composite pipe16-25mm
Expanding/Connecting range:	16x2.2, 20x2.8, 25x3.5, 32x4.4mm
Service interval:	10000cycles
Voltage of battery:	DC 18V,2.0Ah
Connecting cycle time	Approx. 2.5-5S
Charging voltage:	AC 100V~240V ;50~60Hz
Charging time:	Approx.40mins
Weight:	
Tool size:	373x252x97mm
Accessories:	
Battery:	2pcs
Charger:	1pc
Sealing ring of cylinder:	1set
Sealing ring of safety valve:	1set



### SL-1240 Battery Powered Axial Press Tool For axial press Pex and Multi-layer composite pipe

Specifications	
Output:	18kN
Stroke:	PEX pipe:16-32mm
Connecting range:	Multi-Layer composite pipe16-25n
	16x2.2, 20x2.8, 25x3.5, 32x4.4mm
Expanding/Connecting range:	39mm
Service interval:	10000cycles
Voltage of battery:	DC 18V,2.0Ah
Connecting cycle time	Approx. 2.5-5s
Charging voltage:	AC 100V~240V ;50~60Hz
Charging time:	Approx.40mins
Weight:	
Tool size:	364x216x76mm
Accessories:	
Battery:	2pcs
Ch	1,00

1set

Sealing ring of cylinder:

Sealing ring of safety valve:



BATTERY POWERED AXIAL PRESS TOOL





### **SL-2620**Battery Powered Axial Press Tool

For axial press air conditioner pipe Be used in air conditioner, heating, refrigeration system

Rated pressure:	26kN
Connecting range:	φ6.35-28.6mm copper pipe
Charging voltage:	AC 100V~240V ;50~60Hz
Charging time:	Approx.40mins
Hydraulic oil:	35ml
Stroke:	20mm
Service interval:	10000cycles
Voltage of battery:	DC 18V,2.0Ah
Ambient temperature:	-10°C~40°C
Weight:	
Tool size:	331x130x76mm
Accessories:	
Connecting jaws(optional):	6.35、9.52、12.7、15.88、19.05、
	22.2、25.4、28.6mm (Integral type)
Battery:	2 pcs
Charger:	1 pc
Sealing ring of cylinder:	1 set
Sealing ring of safety valve:	1 set



### **SL-4523**Battery Powered Axial Press Tool

For axial press air conditioner pipe Be used in air conditioner, heating, refrigeration system


Rated pressure:	45kN
Stroke:	23mm
Connecting range:	Ф6.35-38.1mm copper pipe
Hydraulic oil:	35ml
Ambient temperature:	-10°C~40°C
Service interval:	10000cycles
Voltage of battery:	DC 18V,2.0Ah
Charging voltage:	AC 100V~240V ;50~60Hz
Charging time:	Approx.40mins
Tool size:	347x155x76mm
Accessories:	
Connecting jaws(optional):	6.35, 9.52, 12.7, 15.88, 19.05, 22.2,
,	25.4, 28.6, 31.8, 34.9, 38.1mm
Battery:	2 pcs
Charger:	1 pc
Sealing ring of cylinder:	1 set
Sealing ring of safety valve:	1 set



### PZ-1240PE Battery Powered Axial Press & Expand Tool

For axial press & expand Pex and Multi-layer composite pipe

pe:16-32mm
Layer composite pipe16-25mn
, 20x2.8, 25x3.5, 32x4.4mm
cycles
/,2 <b>.</b> 0Ah
c. 2.5-5S
0V~240V ;50~60Hz
k.40mins
42x92mm
5
i e
1
2



### PZ-1240 Battery Powered Axial Press Tool For axial press Pex and Multi-layer composite pipe

Specifications 18kN Output: PEX pipe:16-32mm Connecting range: Multi-Layer composite pipe16-25mm 16x2.2, 20x2.8, 25x3.5, 32x4.4mm Connecting range: Connecting stroke: 10000cycles Service interval: DC 18V,2.0Ah Voltage of battery: Approx. 2.5-5S Connecting cycle time AC 100V~240V ;50~60Hz Charging voltage

onarging voltage.	
Charging time:	Approx.40mins
Tool size:	408x216x75mm
Accessories:	
Battery:	2 pcs
Charger:	1 pc
Sealing ring of cylinder:	1 set
Sealing ring of safety valve:	1 set





#### PZ-2620 **Battery Powered Axial Press Tool**

For axial press air conditioner pipe Be used in air conditioner,heating,refrigeration system







Specifications	
Rated pressure:	26kN
Connecting range:	φ6.35-28.6mm copper pipe
Charging voltage:	AC 100V~240V ;50~60Hz
Charging time:	Approx.40mins
Oil capacity:	≈60ml
Stroke:	20mm
Service interval:	10000cycles
Voltage of battery:	DC 18V,2.0Ah
Ambient temperature:	-10°C~40°C
	For axial press Pex and Multi-layer pipe
Weight:	1.94kgs(tool with battery)
Accessories:	
Connecting jaws(optional):	6.35、9.52、12.7、15.88、19.05、
	22.2、25.4、28.6mm (Integral type)
Battery:	2 pcs
Charger:	1 pc
Sealing ring of cylinder:	1 set
Sealing ring of safety valve:	1 set


Kit includes: PZ-2620 AXIAL PRESS TOOL, Connecting jaws, Two 2.0Ah Batteries, One Charger and Carrying Case.





#### PZ-4523 **Battery Powered Axial Press Tool**

For axial press air conditioner pipe Be used in air conditioner, heating, refrigeration system







Specifications	
Rated pressure:	45kN
Stroke:	23mm
Connecting range:	Ф6.35-38.1mm copper pipe
Hydraulic oil:	Shell Tellus T15# S2V Hv15 60ml
Ambient temperature:	-10°C~40°C
Service interval:	10000cycles
Voltage of battery:	DC 18V,2.0Ah
Charging voltage:	AC 100V~240V ;50~60Hz
Charging time:	Approx.40mins
Weight:	4.16kgs(tool with battery)
Tool size:	380x155x75mm
Accessories:	
0 ( 1)	/ DE 0 E0 10 7 1E 00 10 0E 00 0

Connecting jaws(optional):	6.35, 9.52, 12.7, 15.88, 19.05, 22.2,
	25.4, 28.6, 31.8, 34.9, 38.1mm
Battery:	2 pcs
Charger:	1 pc
Sealing ring of cylinder:	1 set
Sealing ring of safety valve:	1 set

- The dies for the tool is optional, there are split type and integral type:
  Split type: 6.35, 9.52, 12.7, 15.88, 19.05, 22.2, 25.4mm
  Integral type: 28.6, 31.8, 34.9, 38.1mm

Kit includes: PZ-4523 AXIAL PRESS TOOL, Connecting jaws, Two 2.0Ah Batteries, One Charger and Carrying Case.





BATTERY POWERED AXIAL PRESS TOOL









FT-1240	Manual Axial Press Tool

- Sliding connections for PEX and Multi-layer composite pipe
- Connecting jaws made of alloy steel with precision casting, ratchet drive makes durable and reliable
- Connecting jaws built-in anti-attrition bushing makes easy sliding
- Expander handle made of high-strength aluminum alloy with precision forging, light and handy



Technical data	
Connecting/Expanding range:	PEX pipe:Φ16-32mm
	Multi-layer pipe:Φ16-25mm
Cutting range:	Max Φ40mm
Weight:	5.2kgs
Stroke:	40mm
Package:	Plastic box
Accessorries	
Connecting jaws:	Φ16x2.2-20x2.8,25x3.5-32x4.4mm
Expanding jaws:	Φ16x2.2-20x2.8,25x3.5,32x4.4mm

#### Kit includes:

ETM-20/ETM-32

Made of steel with precision casting

One axial press tool and expand tool, cutter Two pairs connecting jaws, three expanding jaws and carrying case



FT-1225	Manual Axial Press Tool
F	Manual Axial Press Tool

- Easy changeable sliding jaws
- Smart tool body,easy one handed operation

Technical data	
Connecting range:	Ф12 <b>-</b> 25mm
Expanding range:	Ф12 <b>-</b> 20mm
Cutting range:	Max Φ42mm
Stroke:	80mm
Accessorries	
Jaws:	Ф12,16,20mm

PATENT NO.:ZL 2004 3 0035588.1

Technical data	
ETM-20 Expanding range:	Ф12 <b>-</b> 20mm
ETM-20 Length:	160mm
ETM-20 Weight:	0.33kgs
ETM-32 Expanding range:	Ф16-32mm
ETM-32 Length:	180mm
FTM-32 Weight:	0.58kas



TE-1632	Manual Expand Tool
1 - 1002	i-latitude Expand 1000

• Expander handle made of high-strength aluminum alloy with precision forging, light and handy.

Technical data	
Expanding range:	Ф16-32mm
Expanding dies:	Φ16-20,25,32mm
Length:	395mm
Weight:	1.33kgs



JT-1632	

- 360° rotating head
   Fast Change of crimping die without readjustment by specialfixing system
   With telescope handles, effort-saving

Technical data	
Press force:	40kN
Stroke:	16mm
Package:	Plastic box
Accessorries	
Press die for V type:	Ф12,15,18,22,28mm
Press die for U type:	Ф16,20,25,32mm
Press die for TH type:	Ф16,20,26,32mm

Manual Press Tool

Note:The accessories type used at optional



PE-1632	A4 10 10 10 10 10 10 10 10 10 10 10 10 10
PE-1032	Manual Expand Too

 Expander handle made of high-strength aluminum alloy with precision forging, light and handy.

Technical data	
Expanding range:	Ф16-32mm
Expanding dies:	Ф16,20,25,32mm
Length:	395mm
Weight:	2.12kgs



JT-1626	Manual Press Tool

- Ratchet locking type,ensure accurate reliability press
- Quick-change mounting for simple dies changing
   Antiskid handle structure designed make the press process more comforable

Technical data	
Weight:	2.1kgs
Length:	508mm
Package:	Plastic box
Accessorries:	
Press die for U type:	Φ16,20,25mm
Press die for TH type:	Ф16,20,26mm

Note:The accessories type used at optional

50


Manual Expand Tool

53









Note:The accessories type used at optional



FT-15B/18B/24B PEX Pipe Press Tool			
Technical data			
Model	FT-15B	FT-18B	FT-24B
Press range:	Ф15(3/8")	Ф18[1/2"]	Ф24[3/4"]
Length:	310mm	310mm	310mm
Weight:	1.30kgs	1.30kgs	1.30kgs
Package:	Paper box	Paper box	Paper box




ZT-1824	PEX Pipe Press Tool
Technical data	
Press range:	Ф18(1/2'')-Ф24(3/4'')
Length:	400mm
Weight:	1.20kgs
Package:	Paper box




Package:

FT-15/18/24		PEX Pipe Press Tool	
Technical da	ta		
Model	FT-15	FT-18	FT-24
Press range:	Ф15 (3/8")	Ф18 (1/2")	Ф24 (3/4")
Length:	275mm	275mm	300mm
Weight:	0.9kgs	0.9kgs	1.0 <b>kg</b> s
Package:	Paper box	Paper box	Paper box



Paper box Paper box Paper box



Φ25mm

200mm

0.14kgs

Ф32mm

210mm

0.15kgs

Max cutting range:

Length:

Weight:







**PEX Pipe Press Tool** 

- Stamping handle with heat treatment.Intensify,durable and reliable
- Comfortable skid resistance cover
- Alloy steel forged clamp arm is processed by CNC and strengthen by heat treatment, sturdy and durable

Technical data	
Press range:	Ф18(1/2'')-Ф24(3/4'')
Length:	290mm
Weight:	0.95kgs
Package:	Paper box



FT-1824B	PEX Pipe Press Tool
----------	---------------------

- Stamping handle with heat treatment.Intensify,durable and reliable
- Comfortable skid resistance cover
- Alloy steel forged clamp arm is processed by CNC and strengthen by heat treatment, sturdy and durable

Technical data	
Press range:	Ф18(1/2")-Ф24(3/4")
Length:	400mm
Weight:	1.60kgs
Package:	Paper box




FT-1530	PEX Pipe Press Tool
Mechanical crimping tool for connecting fitting with pipe	

Crimp XPAP, PEX with fittings up to φ30mm

Technical data			
Press range:	Φ15mm(3/8")-30mm(1")		
Press dies:	Φ15mm(3/8"),18mm(1/2"),		
	20mm(5/8"),24mm(3/4"),30mm(1")		
Length:	400mm		
Weight:	1.6kgs		
Package:	Plastic box		



PVC Pipe Cutter
Φ42mm
195mm
0.26kgs



SSC-1530	PEX Pipe Cinch Tool
Technical data	
Cinching range:	3/8",1/2",5/8,",3/4",1"
Weight:	0.6kgs
Length:	278mm
Package:	Blister card

ST-1530	PEX Crimp Ring Removal Tool
Technical data	
Removal range:	Max up to 1"
Weight:	0.3kgs
Length:	220mm
Package:	Blister card

MANUAL TOOL





PS-1632A	Deburring Tool
Technical data	
Features:	For multilayer composite and Pex pipe up to Φ32mm
Deburring range:	Ф16,20,26,32mm





- Cutting device made of steel for long lifetime and with sharp cutting edge
- Large opening for removing pipe chips
- Anodic oxidation aluminium alloy sleeve is light and wear-resisting
- Hexagonal connector for changing different sizes easily,for handle,standard bit connectors or cordless screw driver







Technical data	
Features:	For multilayer composite and Pex pipe up to Φ32mm
Deburring range:	Ф16.20. 26.32mm









PS-40, PS-50	Deburring Tool
Technical data	
PS-40	PS-50
Deburring range:040mm	Deburring range:Φ50mm







Hydraulic Bending Tool	TBJ-32	Manual Bendir
------------------------	--------	---------------

- For accurate one handed bending up to 90°, suit for 10-22mm(1/4"-7/8") thickness below 1.0mm copper pipe
- Ideal in confined spaces

TB-22

- Quick release and resetting of bending formers
- Bending formers easily changed
- Optimal bending results

Technical data			
Former in inch		Former in metric	
Size	Weight	Size	Weight
1/4 "	0.093kgs	10mm	0.087kgs
5/16 "	0.091kgs	12mm	0.113kgs
3/8 "	0.08kgs	14mm	0.146kgs
1/2 "	0.128kgs	15mm	0.141kgs
5/8 "	0.153kgs	16mm	0.14kgs
3/4 "	0.194kgs	18mm	0.193kgs
7/8"	0.222kgs	20mm	0.18kgs
		22mm	0.201kgs

	103-32	Manual Bending 1001
,	For accurate one handed bending up to 90°, suit for copper a	nd XPAP,PEX pipe

- Ideal in confined spaces
- Quick release and resetting of bending formers
   Bending formers easily changed
   Optimal bending results

Technical data			
Former in metric			
Size	Weight	Copper pipe	XPAP,PEX pipe
16mm	0.14kgs	√	√
20mm	0.18kgs	√	√
26mm	0.24kgs	×	√
32mm	0.42kgs	×	√



- For accurate one handed bending up to 90°, suit for 10-22mm[1/4"-7/8"] thickness below 1.5mm copper pipe
- Ideal in confined spaces
- Quick release and resetting of bending formers
- Bending formers easily changedOptimal bending results

Technical data	9		
Former in inch		Former in met	ric
Size	Weight	Size	Weight
1/4 "	0.093kgs	10mm	0.087kgs
5/16 "	0.091kgs	12mm	0.113kgs
3/8 "	0.08kgs	14mm	0.146kgs
1/2 "	0.128kgs	15mm	0.141kgs
5/8 "	0.153kgs	16mm	0.14kgs
3/4 "	0.194kgs	18mm	0.193kgs
7/ 8"	0.222kgs	20mm	0.18kgs
		22mm	0.201kgs





#### **ADVANTAGE OF ZUPPER PRESS JAW**

#### **Connecting Plate** Precision stamping • Security design

**PRESS JAWS** 

#### Serial NO.

• Tracking numbers easier to do after-sales service



#### Precision Forged Jaws

- Made by multi-axis CNC machine
- High strength, sturdy and durable

#### Special heat treatment process

• Inspection control program to ensure long span life

ZUPPER TOOL have a wealth of design and practical experience, can provide customers with differentiated solutions according to customer needs, and to offer customers with pipe press technical support.

#### **SUITABLE PRESS TOOL**

- Compact series press jaws, suit for output 19kN press tool: PZ-1930,BZ-1930,SL-1930,MP-1930,etc
- Another Compact series press jaws, suit for output 24kN press tool: PZ-2430.SL-2430
- Standard series press jaws, suit for output 32kN press tool: PZ-1550,CZ-1550,EB-1550,ED-1550,BZ-1550,HH-1550,HZ-1550,FHT-3240,PZ-3240,etc
- Thicken series press jaws, suit for output 50kN press tool: ED-5050,HH-5050,PZ-5050,etc
- Big size press jaws, suit for output 80kN press tool: ED-60100,HH-60100, FHT-60100







Compact series press jaws

Standard series press jaws

Thicken series press jaws



Big size press jaws



Universal Jaw with interchangeable dies fit for PEX pipe Economic design for any need



Adaptor / Press Rings for 42-54mm

Interchangeable dies

- 1) One universal jaw with different types of dies, with a high cost performance
- 2) Quick change mounting for replace the dies easily

**NOTE:** The economic design only for PEX or PAP pipe, not for stainless pipe and copper pipes.





### THE NEW FLEXIBILITY-ANGLE JAWS Suit for narrow, angled installation areas which are difficult to access

#### **R8 Angle Jaw**

PRESS JAWS

Provide with differentiated solutions according to customers requirment R8 M15, R8 M18, R8 M22, R8 M28, R8 M35 R8 V15, R8 V18, R8 V22, R8 V28, R8 V35......

#### **R8 Rotating Adaptor Jaw**

R8-19(suit for PZ-1930,SL-1930,BZ-1930, etc) R8-24(suit for PZ-2430,SL-2430) R8-32(suit for PZ-3240,PZ-1550,CZ-1550,EB-1550, ED-1550, etc)





Spherical surface connection Swiveling 180-degree-flexibility Precision stamping connecting plate Security design





Standard Series Press Jaws & Press Rings				
DESCRIPTION	JAW SIZE	Weight (KGS)		
	TH16	2.05		
	TH20	2.00		
	TH25	2.05		
PEX& MULTI-LAYER PIPE	TH26	2.05		
	TH32	2.10		
	TH40	2.2		
	TH50	1.9		
	TH63	2.1		

DESCRIPTION	JAW SIZE	Weight (KGS)	
	U16	1.95	
	U20	2.05	
	U25	2.00	
	U32	2.15	
	U40	2.20	
PEX& MULTI-LAYER PIPE	U50	2.8	
	U63	2.47	
	U75	2.6	

DESCRIPTION	JAW SIZE	Weight (KGS)
	SV13	2.01
FOR STAINLESS STEEL	SV20	2.07
PIPE	SV25	2.03
	SV30	-



Special jaws can be made according to your requirements.





Standard Series Pr	ess Jaws & Pres	s Rings	
DESCRIPTION	JAW SIZE	Weight (KGS)	
	VAU15	2.00	
	VAU20	2.06	
	VAU25	2.04	
FOR COPPER PIPE	VAU32	2.09	
16.000112.00112	VAU40	1.48	
	VAU50	1.75	

Standard Series Pr	ess Jaws		
DESCRIPTION	JAW SIZE	Weight (KGS)	
	VUS1/2"	2.00	
	VUS3/4"	2.10	
FOR COPPER PIPE	VUS1"	2.05	
FOR COPPER PIPE	VUS1-1/4"	2.08	
	VUS1-1/2"	2.70	
	VUS2"	3.90	

DESCRIPTION	JAW SIZE	Weight (KGS)	
	M12	2.00	
	M15	2.00	
	M18	1.95	
	M22	2.00	
	M28	2.00	
FOR STAINLESS STEEL	M35	2.05	
/COPPER PIPE	M42	1.35	
	M54	1.60	

Standard Series Pr	ess Jaws		
DESCRIPTION	JAW SIZE	Weight (KGS)	
	V12	2.02	
	V15	1.95	
	V18	2.10	
	V22	2.05	
	V28	2.00	
FOR STAINLESS STEEL	V35	2.05	
/COPPER PIPE	V42	1.40	
	V54	1.63	

DESCRIPTION	JAW SIZE	Weight (KGS)	
	SDR13	2.0	
	SDR20	2.1	
FOR CTAINII FCC CTFFI	SDR25	2.05	
FOR STAINLESS STEEL /COPPER PIPE	SDR30	1.25	69/
	SDR40	1.45	
	SDR50	1.6	
	SDR60	1.9	

Compact Series Pr	ess Jaws		
DESCRIPTION	JAW SIZE	Weight (KGS)	
	TH16	1.27	
	TH20	1.33	
PEX& MULTI-LAYER PIPE	TH25	1.41	
	TH26	1.35	
	TH32	1.40	

PRESS JAWS






Compact Series P	ress Jaws		
DESCRIPTION	JAW SIZE	Weight (KGS)	
PEX& MULTI-LAYER PIPE	U16	1.20	
PEX& MULTI-LATER PIPE	U20	1.29	
	U25	1.30	
	U32	1.50	

DESCRIPTION	JAW SIZE	Weight (KGS)
	M12	1.23
	M15	1.30
FOR STAINLESS STEEL	M18	1.29
/COPPER PIPE	M22	1.37
	M28	1.39
	M35	1.40



DESCRIPTION	JAW SIZE	Weight (KGS)
	V12	1.23
FOR STAINLESS STEEL	V15	1.23
/COPPER PIPE	V18	1.29
	V22	1.38
	V28	1.47



DESCRIPTION	JAW SIZE	Weight (KGS)
	SV13	1.23
FOR STAINLESS STEEL	SV20	1.27
PIPE	SV25	1.34
	SV30	-



DESCRIPTION	JAW SIZE	Weight (KGS)
	VAU15	1.23
FOR COPPER PIPE	VAU20	1.28
	VAU25	1.35
	VAU32	1.49



Compact Series P	ress Jaws		
DESCRIPTION	JAW SIZE	Weight (KGS)	
FOR COPPER PIPE	VUS1/2"	1.23	
	VUS3/4"	1.26	
	VUS1"	1.48	

Big size Press Jaws				
DESCRIPTION	JAW SIZE	Weight (KGS)		
FOR STAINLESS STEEL PIPE	S63.5	3.05		
	S76.1	3.7		
	S88.9	4.1		
	S101.6	5.5		
	S108	5.7		
FOR STAINLESS STEEL PIPE	M67	3.5		
	M76.1	3.9		
	M88.9	4.35		
	M108	5.7		
FOR STAINLESS STEEL PIPE	SDR80	4.4		
	SDR100	5.6		

PRESS JAWS