


AH-16WF

Technical data

Scope of use:	Wire Ferrule End Sleeves
Crimping range:	6-16mm ²
Length:	260mm
Weight:	0.6kgs



AH-35WF

Technical data

Scope of use:	Wire Ferrule End Sleeves
Crimping range:	10-35mm ²
Length:	260mm
Weight:	0.6kgs



AH-004

Technical data


Scope of use:	Non-insulated Terminal
Crimping range:	0.5-10mm ²
Length:	260mm
Weight:	0.6kgs



AH-005

Technical data

Scope of use:	Non-insulated Terminal
Crimping range:	0.5-10mm ²
Length:	260mm
Weight:	0.6kgs



AH-006

Technical data


Scope of use:	Pre-insulated Terminal and Connector
Crimping range:	0.5-6mm ²
Length:	260mm
Weight:	0.6kgs



AH-03C

Technical data

Scope of use:	Pre-insulated Terminal
Crimping range:	0.5-6mm ²
Length:	260mm
Weight:	0.6kgs



AH-03B

Technical data

Scope of use:	Non-insulated Terminal and Connector
Crimping range:	0.5-6mm ²
Length:	260mm
Weight:	0.6kgs



AH-10

Technical data

Scope of use:	Non-insulated Terminal and Connector
Crimping range:	1.5-10mm ²
Length:	260mm
Weight:	0.6kgs