



### KYQ-300C

SAFETY SYSTEM INSIDE

- With safety valve inside
- With interchangeable dies for different size
- The tool clicks when the pressure reaches its limit
- The head can rotate 180°

#### Technical data

Crimping range:	Cu 16-300mm <sup>2</sup>
Crimping force:	100kN
Stroke:	18mm
Crimping type:	Hexagon Crimping

#### Accessories:

Crimping dies:	16,25,35,50,70,95,120,150,185,240,300mm <sup>2</sup>
Sealing O-ring:	One Set

### KYQ-400

SAFETY SYSTEM INSIDE

- With safety valve inside
- With interchangeable dies for different size
- The tool clicks when the pressure reaches its limit
- The head can rotate 180°

#### Technical data

Crimping range:	50-400mm <sup>2</sup>
Crimping force:	105kN
Stroke:	32mm
Crimping type:	Hexagon Crimping

#### Accessories:

Crimping dies:	50,70,95,120,150,185,240,300,400mm <sup>2</sup>
Sealing O-ring:	One Set



### FHT-400U

- U Type of split crimping head, with interchangeable dies
- Suitable for transmission and distribution of indoor and outdoor projects
- The tool work for different kind of connecting and building over head cable

#### Technical data

Crimping range:	Cu16-400mm <sup>2</sup>
Crimping force:	120kN
Working pressure:	70Mpa
Stroke:	20mm

#### Accessories:

Crimping dies:	16,25,35,50,70,95,120,150,185,240,300,400mm <sup>2</sup>
Sealing O-ring:	One Set

Note: It Can Match Hand Pump

### FHT-300

- U Type of split crimping head, with interchangeable dies
- Suitable for transmission and distribution of indoor and outdoor projects
- The tool work for different kind of connecting and building over head cable

#### Technical data

Crimping range:	16-300mm <sup>2</sup>
Crimping force:	60kN
Stroke:	17mm
Crimping type:	Hexagon Crimping

#### Accessories:

Crimping dies:	16,25,35,50,70,95,120,150,185,240,300mm <sup>2</sup>
Sealing O-ring:	One Set

Note: It Can Match Hand Pump

### FHT-60UNV

- Universal head with quick coupling, rotates 360°, flip top style
- For connecting to hydraulic drive units with 70 Mpa operating pressure for the best possible crimping, cutting and punching results

#### Technical data

Crimping range:	16-300mm <sup>2</sup>
Cutting range:	φ40mm for Cu/Al cable and armoured Cu/Alcable.
Punching range:	φ22.5-61.5mm in the 3.5mm mild steel
Crimping force:	60kN
Stroke:	42mm

#### Accessories:

Crimping dies:	16,25,35,50,70,95,120,150,185,240,300mm <sup>2</sup>
Punches&dies(TypeD):	22.5,28.3,34.6,43.2,49.6,61.5mm
Sealing O-ring:	One Set