



### HT-150

SAFETY SYSTEM INSIDE

- Flip top style head, rotates 180°
- With safety valve inside to avoid overload

#### Technical data

Crimping range:	Cu 4-150mm <sup>2</sup>
Crimping force:	35kN
Length:	215mm
Crimping type:	Hexagon Crimping

#### Accessories:

Crimping dies:	4,6,8,10,16,25,35,50,70,95,120,150mm <sup>2</sup>
----------------	---



### THS-150

- Flip top style head, rotates 180°
- With safety valve inside to avoid overload

#### Technical data

Crimping range:	Cu10-150mm <sup>2</sup>
Crimping force:	60kN

#### Accessories:

Crimping dies:	10-16,25-35,50-70,95-120,150mm <sup>2</sup>
----------------	---



### CYO-6B

Up to 240mm<sup>2</sup>

- Quad-point indent crimping feature, no die required
- The head can rotate 350°
- With Safety valve, twist the active handle to release the pressure  
Suitable for crimping tubular cable lugs and connectors "standard type" and fine and superfine stranded conductors to 240mm<sup>2</sup>

#### Technical data

Crimping range:	Cu10-240mm <sup>2</sup>
Crimping force:	60kN
Stroke:	35mm



### CYO-430

SAFETY SYSTEM INSIDE

- Two stage hydraulic system with fast feed and power stroke, With Safety valve, twist the active handle to release the pressure

#### Technical data

Crimping force:	116kN
Crimping range:	Cu50-400mm <sup>2</sup>
Stroke:	30mm
Oil capacity:	145cc

#### Accessories:

Crimping dies:	50,70,95,120,150,185,240,300,400mm <sup>2</sup>
----------------	---