



COMPACT DESIGN, 180° x 360° SWIVELLING HEAD EFFORTLESS PUNCH WITH 6TON OUTPUT

SL-6AL Battery Powered Punching Tool

Aluminum alloy body with light weight

180°x360°swivelling head

Ergonomic design with high quality aviation aluminum

Technical data	SL-6AL
Rated pressure:	60kN
Stroke:	25mm
Cycles/charge:	250cycles(Max.mild steel 3mm, Φ49.6mm)
Piston rod thread:	3/4-19 UN
Max. Round Punch Size :	61.5mm Dia. in 3.5mm mild steel 161.9mm Dia. in 2mm mild steel 61.5mm Dia. in 2mm stainless steel
Voltage/capacity:	18V/2.0Ah
Charging time:	40 mins
Charging voltage:	AC 100V-240V ;50-60Hz
Package:	Plastic box
Weight	
Tool Size:	417x128x76mm

DESCRIPTION	HOLE SIZE (TYPE D)		
	Φ(INCH)	Φmm	
1/2" Conduit Size Punch&Die	7/8"	0.885	22.50
3/4" Conduit Size Punch&Die		1.115	28.30
1" Conduit Size Punch&Die		1.362	34.60
1-1/4" Conduit Size Punch&Die		1.701	43.20
1-1/2" Conduit Size Punch&Die	1-15/16"	1.951	49.60
2" Conduit Size Punch&Die	2-3/8"	2.146	61.50
7/16"x3/4" Draw Stud			1pc
3/4"x3/4" Draw Stud			1pc
Spacer			1pc
Battery:			2 pcs
Charger:			1pc
Sealing ring of cylinder:			1set
Sealing ring of safety valve:			1set

