



TC-38

- Strong, light weight glass fiber handle
- Adjustable pivot bolt realized adjustable blade
- Changeable, forging blade heat treated and precise polish

Technical data

Cutting range:	
Cu cable	
Max. cutting 400mm ² , normal for cutting 240mm ²	
Al cable	
Max. cutting 500mm ² , normal for cutting 400mm ²	
Communication cable Max. cutting 11/2" (φ38mm)	
Length:	800mm
Weight:	2.8kg

Note: In order to meet the demand please provide appropriate size and a standard of tube when place order.



TC-125S/250S

- Only cut Cu/Al Cable with telescopic handle

Technical data

Item No:	TC-125S	TC-250S
Cutting range:	120mm ² for Cu/Al conductor	240mm ² for Cu/Al conductor
Length:	300-400mm	415-565mm
Weight:	1.25kg	2.3kg




TCR-500S

- Using ratchet drive device with telescopic handle, only for cut Cu/Al cable

Technical data

Cutting range:	500mm ² for Cu conductor
	400mm ² for Al conductor
Length:	240-290mm
Weight:	0.98kg




ZC-36A/ZC-60A

- Forged blade, long span life, easy for cutting
- Only for cutting Cu/Al cable, forbid cut steel wire, hardened copper wire

Technical data

Item No:	ZC-36A	ZC-60A
Cutting range:	φ36mm / 300mm ²	φ60mm / 400mm ²
Length:	260mm	320mm
Weight:	0.6kg	0.8kg
Package:	Blister card	Blister card

Note: Only cutting for single or multi-stranded Cu/Al cable. Do not cutting for steel wire and hard copper wire.




ZC-32A/ZC-52A

- Forged blade, long span life, easy for cutting
- Only for cutting Cu/Al cable, forbid cut steel wire, hardened copper wire

Technical data

Item No:	ZC-32A	ZC-52A
Cutting range:	φ32mm / 240mm ²	φ48mm / 400mm ²
Length:	360mm	415mm
Weight:	0.7kg	1.2kg
Package:	Blister card	Blister card

Note: Only cutting for single or multi-stranded Cu/Al cable. Do not cutting for steel wire and hard copper wire.



ZC-70A

- Forged blade, long span life, easy for cutting

Technical data

Cutting range:	φ70mm for Cu/Al armoured cable
Weight:	3.2kgs
Length:	380-485mm
Package:	Canvas bag